













SOIL BORING LOG AND MONITORING WELL COMPLETION DETAILS						Soil Boring: BH-8																																																									
Project Name: Fmr. Budway Trucking			Project Location: 1015 Chesley Ave., Richmond, CA			Page 1 of 1																																																									
Driller: Vironex, Inc.			Type of Rig: Direct Push		Size of Drill: 2.5" Diameter																																																										
Logged By: Damian Hriciga			Date Drilled: August 15, 2003		Checked By: Robert E. Kitay, R.G.																																																										
WATER AND WELL DATA				Total Depth of Well Completed: NA																																																											
Depth of Water First Encountered: 6.5'				Well Screen Type and Diameter: NA																																																											
Static Depth of Water in Well: 5'				Well Screen Slot Size: NA																																																											
Total Depth of Boring: 10'				Type and Size of Soil Sampler: 2" Macro-Core																																																											
<table><tr><th rowspan="2">Depth in Feet</th><th rowspan="2">BORING DETAIL</th><th rowspan="2">Description</th><th colspan="5">SOIL/ROCK SAMPLE DATA</th><th rowspan="2">Depth in Feet</th><th colspan="1">DESCRIPTION OF LITHOLOGY</th></tr><tr><th>Interval</th><th>Blow Counts</th><th>OVM (ppmv)</th><th>Water Level</th><th>Graphic Log</th><th>standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.</th></tr></table>								Depth in Feet	BORING DETAIL	Description	SOIL/ROCK SAMPLE DATA					Depth in Feet	DESCRIPTION OF LITHOLOGY	Interval	Blow Counts	OVM (ppmv)	Water Level	Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.																																								
Depth in Feet	BORING DETAIL	Description	SOIL/ROCK SAMPLE DATA								Depth in Feet	DESCRIPTION OF LITHOLOGY																																																			
			Interval	Blow Counts	OVM (ppmv)	Water Level	Graphic Log	standard classification, texture, relative moisture, density, stiffness, odor-staining, USCS designation.																																																							
<table><tr><td rowspan="5">0</td><td rowspan="5"></td><td rowspan="5">Class "H" Portland Cement</td><td rowspan="5"></td><td rowspan="5">0</td><td rowspan="5"></td><td rowspan="5"></td><td rowspan="5">0</td><td>0</td><td>Asphalt</td></tr><tr><td>1</td><td>Silty CLAY (CH); dark grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor</td></tr><tr><td>4</td><td>Clayey SAND (SC); yellow brown; loose; damp; 85% medium-coarse sand; 15% clay; non-plastic; medium estimated K; no odor</td></tr><tr><td>5</td><td>Silty CLAY (CH); grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor</td></tr><tr><td>7</td><td>Clayey SAND (SC); grey; loose; wet; 80% coarse sand; 10% clay; 10% silt; non-plastic; medium estimated K; no odor</td></tr><tr><td>10</td><td>Silty CLAY (CH); brown; soft; wet; 80% clay; 20% silt; moderate plasticity; low estimated K; no odor</td></tr><tr><td>15</td><td colspan="7">End of boring at 10'</td><td>15</td></tr><tr><td>20</td><td colspan="7"></td><td>20</td></tr><tr><td>25</td><td colspan="7"></td><td>25</td></tr><tr><td>30</td><td colspan="7"></td><td>30</td></tr></table>								0		Class "H" Portland Cement		0			0	0	Asphalt	1	Silty CLAY (CH); dark grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor	4	Clayey SAND (SC); yellow brown; loose; damp; 85% medium-coarse sand; 15% clay; non-plastic; medium estimated K; no odor	5	Silty CLAY (CH); grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor	7	Clayey SAND (SC); grey; loose; wet; 80% coarse sand; 10% clay; 10% silt; non-plastic; medium estimated K; no odor	10	Silty CLAY (CH); brown; soft; wet; 80% clay; 20% silt; moderate plasticity; low estimated K; no odor	15	End of boring at 10'							15	20								20	25								25	30								30
0		Class "H" Portland Cement		0			0									0	Asphalt																																														
																1	Silty CLAY (CH); dark grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor																																														
																4	Clayey SAND (SC); yellow brown; loose; damp; 85% medium-coarse sand; 15% clay; non-plastic; medium estimated K; no odor																																														
																5	Silty CLAY (CH); grey; stiff; damp; 95% clay; 5% silt; high plasticity; very low estimated K; no odor																																														
								7	Clayey SAND (SC); grey; loose; wet; 80% coarse sand; 10% clay; 10% silt; non-plastic; medium estimated K; no odor																																																						
10	Silty CLAY (CH); brown; soft; wet; 80% clay; 20% silt; moderate plasticity; low estimated K; no odor																																																														
15	End of boring at 10'							15																																																							
20								20																																																							
25								25																																																							
30								30																																																							
AQUA SCIENCE ENGINEERS, INC.																																																															